

Marshall County, MN Floodplain Management Ordinance  
Three Districts, Two-Map Format

TABLE OF CONTENTS

	PAGE
SECTION 1.0 STATUTORY AUTHORIZATION, FINDINGS OF FACT AND PURPOSE	1
1.1 Statutory Authorization	1
1.2 Findings of Fact	1
1.3 Statement of Purpose	1
SECTION 2.0 GENERAL PROVISIONS	1
2.1 Lands to Which Ordinance Applies	1
2.2 Establishment of Official Zoning Map	1
2.3 Regulatory Flood Protection Elevation	2
2.4 Interpretation	2
2.5 Abrogation and Greater Restrictions	2
2.6 Warning and Disclaimer of Liability	2
2.7 Severability	2
2.8 Definitions	3
SECTION 3.0 ESTABLISHMENT OF ZONING DISTRICTS	5
3.1 Districts	5
3.2 Compliance	5
SECTION 4.0 FLOODWAY DISTRICT (FW)	6
4.1 Permitted Uses	6
4.2 Standards for Floodway Permitted Uses	6
4.3 Conditional Uses	6
4.4 Standards for Floodway Conditional Uses	7
SECTION 5.0 FLOOD FRINGE DISTRICT (FF)	8
5.1 Permitted Uses	8
5.2 Standards for Flood Fringe Permitted Uses	8
5.3 Conditional Uses	9
5.4 Standards for Flood Fringe Conditional Uses	9
5.5 Standards for All Flood Fringe Uses	10

SECTION 6.0	GENERAL FLOOD PLAIN DISTRICT	11
6.1	Permissible Uses	11
6.2	Procedures for Floodway and Flood Fringe Determinations	11
SECTION 7.0	SUBDIVISIONS	12
7.1	Land Suitability Review Criteria	12
7.2	Requirements for Floodway/Flood Fringe Determinations	12
7.3	Removal of Special Flood Hazard Area Designation	13
SECTION 8.0	UTILITIES, RAILROADS, ROADS, AND BRIDGES	13
8.1	Public Utilities	13
8.2	Public Transportation Facilities	13
8.3	On-site Sewage Treatment and Water Supply Systems	13
SECTION 9.0	MANUFACTURED HOMES/TRAVEL TRAILERS AND TRAVEL VEHICLES	13
9.1	New Manufactured Home Parks	13
9.2	Replacement Manufactured Homes- Existing Parks	13
9.3	Recreational Vehicles	13
SECTION 10.0	ADMINISTRATION	15
10.1	Zoning Administrator	15
10.2	Permits, Certification Requirements and Record Keeping	15
10.3	Appeals and Variances/Duties of the Board of Adjustment	16
10.4	Conditional Uses-Standards and Evaluation Procedures	17
SECTION 11.0	NONCONFORMING USES	19
SECTION 12.0	PENALTIES FOR VIOLATION	20
SECTION 13.0	AMENDMENTS	21

**MARSHALL COUNTY FLOOD PLAIN MANAGEMENT ORDINANCE  
THREE DISTRICT, TWO - MAP FORMAT<sup>1</sup>**

<sup>1</sup>*A Flood Insurance Rate Map and Flood Boundary and Floodway Map have been published for the community.  
The Regulatory Floodway boundary is shown on the Flood Boundary and Floodway Map.*

**SECTION 1.0 STATUTORY AUTHORIZATION, FINDINGS OF FACT AND PURPOSE**

1.1 Statutory Authorization: The legislature of the State of Minnesota has, in Minnesota Statutes Chapter 103F and Chapter 394, delegated the responsibility to local government units to adopt regulations designed to minimize flood losses. Therefore, the Board of Commissioners of Marshall County, Minnesota does ordain as follows:

1.2 Findings of Fact:

- 1.21 The flood hazard areas of Marshall County, Minnesota, are subject to periodic inundation which results in potential loss of life, loss of property, health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures for flood protection and relief, and impairment of the tax base, all of which adversely affect the public health, safety, and general welfare.
- 1.22 Methods Used to Analyze Flood Hazards. This Ordinance is based upon a reasonable method of analyzing flood hazards which is consistent with the standards established by the Minnesota Department of Natural Resources.
- 1.23 National Flood Insurance Program Compliance. This Ordinance is adopted to comply with the rules and regulations of the National Flood Insurance Program codified as 44 Code of Federal Regulations Parts 59 -78, as amended, so as to maintain the community's eligibility in the National Flood Insurance Program.

1.3 Statement of Purpose: It is the purpose of this Ordinance to promote the public health, safety, and general welfare and to minimize those losses described in Section 1.21 by provisions contained herein.

**SECTION 2.0 GENERAL PROVISIONS**

2.1 Lands to Which Ordinance Applies: This Ordinance shall apply to all lands within the jurisdiction of Marshall County shown on the Official Zoning Map and/or the attachments thereto as being located within the boundaries of the Floodway, Flood Fringe, or General Flood Plain Districts.

2.2 Establishment of Official Zoning Map: The Official Zoning Map together with all materials attached thereto is hereby adopted by reference and declared to be a part of this Ordinance. The attached material shall include the Flood Insurance Study for the County of Marshall prepared by the Federal Emergency Management Agency dated 10/16/87, and the Flood Boundary and Floodway Map and Flood Insurance Rate Map dated 07/18/83 and revised community Flood Insurance Rate Map and Flood Boundary and Floodway Map panel maps #270638-0345 dated 10/16/87, therein. The Official Zoning Map shall be on file in the Office of the Marshall County Auditor-Treasurer and Zoning Administrator.

(Note: If a community has annexed an area that is not shown on the flood insurance rate map adopted in Section 2.2 above, the community is advised to determine if the Federal Emergency Management Agency

has published a flood insurance rate map and flood boundary and floodway map for the adjoining city or the unincorporated areas of the county. If the Federal Emergency Management Agency has designated floodplain areas for the annexed area on an adjoining community's flood insurance rate map and flood boundary and floodway map, then the respective adjoining community's flood insurance rate map and flood boundary and floodway map panels (and flood insurance study text, if available) must also be adopted by reference in Section 2.2.

If a community is anticipating future annexations of floodplain areas, the community is similarly advised to adopt the flood insurance rate map and flood boundary and floodway map panels for the adjoining community(ies) along with a statement that these maps, in concert with the regulatory language in this Ordinance, will be used for floodplain management in the annexed area.)

**2.3 Regulatory Flood Protection Elevation:** The regulatory flood protection elevation shall be an elevation no lower than one foot above the elevation of the regional flood plus any increases in flood elevation caused by encroachments on the flood plain that result from designation of a floodway.

**2.4 Interpretation:**

2.41 In their interpretation and application, the provisions of this Ordinance shall be held to be minimum requirements and shall be liberally construed in favor of the Governing Body and shall not be deemed a limitation or repeal of any other powers granted by state statutes.

2.42 The boundaries of the zoning districts shall be determined by scaling distances on the Official Zoning Map. Where interpretation is needed as to the exact location of the boundaries of the district as shown on the Official Zoning Map, as for example where there appears to be a conflict between a mapped boundary and actual field conditions and there is a formal appeal of the decision of the Zoning Administrator, the Board of Adjustment shall make the necessary interpretation. All decisions will be based on elevations on the regional (100-year) flood profile, the ground elevations that existed on the site at the time the Community adopted its initial floodplain ordinance, and other available technical data. Persons contesting the location of the district boundaries shall be given a reasonable opportunity to present their case to the Board of Adjustment and to submit technical evidence.

**2.5 Abrogation and Greater Restrictions:** It is not intended by this Ordinance to repeal, abrogate, or impair any existing easements, covenants, or deed restrictions. However, where this Ordinance imposes greater restrictions, the provisions of this Ordinance shall prevail. All other ordinances inconsistent with this Ordinance are hereby repealed to the extent of the inconsistency only.

**2.6 Warning and Disclaimer of Liability:** This Ordinance does not imply that areas outside the flood plain districts or land uses permitted within such districts will be free from flooding or flood damages. This Ordinance shall not create liability on the part of Marshall County or any officer or employee thereof for any flood damages that result from reliance on this Ordinance or any administrative decision lawfully made thereunder.

**2.7 Severability:** If any section, clause, provision, or portion of this Ordinance is adjudged unconstitutional or invalid by a court of competent jurisdiction, the remainder of this Ordinance shall not be affected thereby.

2.8 Definitions: Unless specifically defined below, words or phrases used in this Ordinance shall be interpreted so as to give them the same meaning as they have in common usage and so as to give this Ordinance its most reasonable application.

- 2.811 Accessory Use or Structure - a use or structure on the same lot with, and of a nature customarily incidental and subordinate to, the principal use or structure.
- 2.812 Basement - means any area of a structure, including crawl spaces, having its floor or base subgrade (below ground level) on all four sides, regardless of the depth of excavation below ground level.
- 2.813 Conditional Use - means a specific type of structure or land use listed in the official control that may be allowed but only after an in-depth review procedure and with appropriate conditions or restrictions as provided in the official zoning controls or building codes and upon a finding that:
  - (a) Certain conditions as detailed in the zoning ordinance exist.
  - (b) The structure and/or land use conform to the comprehensive land use plan if one exists and are compatible with the existing neighborhood.
- 2.814 Equal Degree of Encroachment - a method of determining the location of floodway boundaries so that flood plain lands on both sides of a stream are capable of conveying a proportionate share of flood flows.
- 2.815 Flood - a temporary increase in the flow or stage of a stream or in the stage of a wetland or lake that results in the inundation of normally dry areas.
- 2.816 Flood Frequency - the frequency for which it is expected that a specific flood stage or discharge may be equaled or exceeded.
- 2.817 Flood Fringe - that portion of the flood plain outside of the floodway. Flood fringe is synonymous with the term "floodway fringe" used in the Flood Insurance Study for Marshall County.
- 2.818 Flood Plain - the beds proper and the areas adjoining a wetland, lake or watercourse which have been or hereafter may be covered by the regional flood.
- 2.819 Flood Proofing - a combination of structural provisions, changes, or adjustments to properties and structures subject to flooding, primarily for the reduction or elimination of flood damages.
- 2.820 Floodway - the bed of a wetland or lake and the channel of a watercourse and those portions of the adjoining flood plain which are reasonably required to carry or store the regional flood discharge.
- 2.821 Lowest Floor - the lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, used solely for parking of vehicles, building access, or storage in an area other than a basement area, is not considered a building's lowest floor.
- 2.822 Manufactured Home - a structure, transportable in one or more sections, which is built on a permanent chassis and is designed for use with or without a permanent foundation when attached to the required utilities. The term "manufactured home" does not include the term "recreational vehicle."

- 2.823 Obstruction - any dam, wall, wharf, embankment, levee, dike, pile, abutment, projection, excavation, channel modification, culvert, building, wire, fence, stockpile, refuse, fill, structure, or matter in, along, across, or projecting into any channel, watercourse, or regulatory flood plain which may impede, retard, or change the direction of the flow of water, either in itself or by catching or collecting debris carried by such water.
- 2.824 Principal Use of Structure - means all uses or structures that are not accessory uses or structures.
- 2.825 Reach - a hydraulic engineering term to describe a longitudinal segment of a stream or river influenced by a natural or man-made obstruction. In an urban area, the segment of a stream or river between two consecutive bridge crossings would most typically constitute a reach.
- 2.826 Recreational Vehicle - a vehicle that is built on a single chassis, is 400 square feet or less when measured at the largest horizontal projection, is designed to be self-propelled or permanently towable by a light duty truck, and is designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use. For the purposes of this Ordinance, the term recreational vehicle shall be synonymous with the term travel trailer/travel vehicle.
- 2.827 Regional Flood - a flood which is representative of large floods known to have occurred generally in Minnesota and reasonably characteristic of what can be expected to occur on an average frequency in the magnitude of the 100-year recurrence interval. Regional flood is synonymous with the term "base flood" used in a flood insurance study.
- 2.828 Regulatory Flood Protection Elevation - The regulatory flood protection elevation shall be an elevation no lower than one foot above the elevation of the regional flood plus any increases in flood elevation caused by encroachments on the flood plain that result from designation of a floodway.
- 2.829 Structure - anything constructed or erected on the ground or attached to the ground or on-site utilities, including, but not limited to, buildings, factories, sheds, detached garages, cabins, manufactured homes, recreational vehicles not meeting the exemption criteria specified in Section 9.31 of this Ordinance and other similar items.
- 2.830 Variance - means a modification of a specific permitted development standard required in an official control including this Ordinance to allow an alternative development standard not stated as acceptable in the official control, but only as applied to a particular property for the purpose of alleviating a hardship, practical difficulty or unique circumstance as defined and elaborated upon in a community's respective planning and zoning enabling legislation.

## **SECTION 3.0 ESTABLISHMENT OF ZONING DISTRICTS**

### **3.1 Districts:**

- 3.11 Floodway District. The Floodway District shall include those areas designated as floodway on the Flood Boundary and Floodway Map adopted in Section 2.2 of this Ordinance.

- 3.12 Flood Fringe District. The Flood Fringe District shall include those areas designated as floodway fringe on the Flood Boundary and Floodway Map adopted in Section 2.2 of this Ordinance.
- 3.13 General Flood Plain District. The General Flood Plain District shall include those areas designated as Zone A on the Flood Insurance Rate Map adopted in Section 2.2 and those areas designated as Zone A1-A30, Zone A0, or Zone AH on the Flood Insurance Rate Map where a floodway/flood fringe boundary has not been designated on the Flood Boundary and Floodway Maps adopted in Section 2.2 of this Ordinance.

3.2 Compliance: No new structure or land shall hereafter be used and no structure shall be constructed, located, extended, converted, or structurally altered without full compliance with the terms of this Ordinance and other applicable regulations which apply to uses within the jurisdiction of this Ordinance. Within the Floodway, Flood Fringe and General Flood Plain Districts, all uses not listed as permitted uses or conditional uses in Sections 4.0, 5.0 and 6.0 that follow, respectively, shall be prohibited. In addition, a caution is provided here that:

- 3.21 New manufactured homes, replacement manufactured homes and certain recreational vehicles are subject to the general provisions of this Ordinance and specifically Section 9.0;
- 3.22 Modifications, additions, structural alterations, and repair, or repair after damage to existing nonconforming structures and nonconforming uses of structures or land are regulated by the general provisions of this Ordinance and specifically Section 11.0; and
- 3.23 As-built elevations for elevated or flood proofed structures must be certified by ground surveys and flood proofing techniques must be designed and certified by a registered professional engineer or architect as specified in the general provisions of this Ordinance and specifically as stated in Section 10.0 of this Ordinance.

## **SECTION 4.0 FLOODWAY DISTRICT (FW)**

### 4.1 Permitted Uses:

- 4.11 General farming, pasture, grazing, outdoor plant nurseries, horticulture, truck farming, forestry, sod farming, and wild crop harvesting.
- 4.12 Industrial-commercial loading areas, parking areas, and airport landing strips.
- 4.13 Private and public golf courses, tennis courts, driving ranges, archery ranges, picnic grounds, boat launching ramps, swimming areas, parks, wildlife and nature preserves, game farms, fish hatcheries, shooting preserves, target ranges, trap and skeet ranges, hunting and fishing areas, and single or multiple purpose recreational trails.
- 4.14 Residential lawns, gardens, parking areas, and play areas.

### 4.2 Standards for Floodway Permitted Uses:

- 4.21 The use shall have a low flood damage potential.

- 4.22 The use shall be permissible in the underlying zoning district if one exists.
- 4.23 The use shall not obstruct flood flows or increase flood elevations and shall not involve structures, fill, obstructions, excavations or storage of materials or equipment.

#### 4.3 Conditional Uses:

- 4.31 Structures accessory to the uses listed in 4.1 above and the uses listed in 4.32 - 4.38 below.
- 4.32 Extraction and storage of sand, gravel, and other materials.
- 4.33 Marinas, boat rentals, docks, piers, wharves, and water control structures.
- 4.34 Railroads, streets, bridges, utility transmission lines, and pipelines.
- 4.35 Storage yards for equipment, machinery, or materials.
- 4.36 Placement of fill.
- 4.37 Recreational vehicles either on individual lots of record or in existing or new subdivisions or commercial or condominium type campgrounds, subject to the exemptions and provisions of Section 9.3 of this Ordinance.
- 4.38 Structural works for flood control such as levees, dikes and floodwalls constructed to any height where the intent is to protect individual structures and levees or dikes where the intent is to protect agricultural crops for a frequency flood event equal to or less than the 10-year frequency flood event.

#### 4.4 Standards for Floodway Conditional Uses:

- 4.41 All Uses. No structure (temporary or permanent), fill (including fill for roads and levees), deposit, obstruction, storage of materials or equipment, or other uses may be allowed as a conditional use that will cause any increase in the stage of the 100-year or regional flood or cause an increase in flood damages in the reach or reaches affected.
- 4.42 All floodway conditional uses shall be subject to the procedures and standards contained in Section 10.4 of this Ordinance.
- 4.43 The conditional use shall be permissible in the underlying zoning district if one exists.
- 4.44 Fill:
  - (a) Fill, dredge spoil, and all other similar materials deposited or stored in the flood plain shall be protected from erosion by vegetative cover, mulching, riprap or other acceptable method.
  - (b) Dredge spoils sites and sand and gravel operations shall not be allowed in the floodway unless a long-term site development plan is submitted which includes an erosion/sedimentation prevention element to the plan.
  - (c) As an alternative, and consistent with Subsection (b) immediately above, dredge spoil disposal and sand and gravel operations may allow temporary, on-site storage of fill or other materials which would have caused an increase to the stage of the 100-year or regional flood but only

after the Governing Body has received an appropriate plan which assures the removal of the materials from the floodway based upon the flood warning time available. The conditional use permit must be title registered with the property in the Office of the County Recorder.

4.45 Accessory Structures:

- (a) Accessory structures shall not be designed for human habitation.
- (b) Accessory structures, if permitted, shall be constructed and placed on the building site so as to offer the minimum obstruction to the flow of flood waters:
  - (1) Whenever possible, structures shall be constructed with the longitudinal axis parallel to the direction of flood flow; and
  - (2) So far as practicable, structures shall be placed approximately on the same flood flow lines as those of adjoining structures.
- (c) Accessory structures shall be elevated on fill or structurally dry flood proofed in accordance with the FP-1 or FP-2 flood proofing classifications in the State Building Code. As an alternative, an accessory structure may be flood proofed to the FP-3 or FP-4 flood proofing classification in the State Building Code provided the accessory structure constitutes a minimal investment, does not exceed 500 square feet in size at its largest projection, and for a detached garage, the detached garage must be used solely for parking of vehicles and limited storage. All flood proofed accessory structures must meet the following additional standards:
  - (1) The structure must be adequately anchored to prevent flotation, collapse or lateral movement of the structure and shall be designed to equalize hydrostatic flood forces on exterior walls;
  - (2) Any mechanical and utility equipment in a structure must be elevated to or above the regulatory flood protection elevation or properly flood proofed; and
  - (3) To allow for the equalization of hydrostatic pressure, there must be a minimum of two “automatic” openings in the outside walls of the structure having a total net area of not less than one square inch for every square foot of enclosed area subject to flooding. There must be openings on at least two sides of the structure and the bottom of all openings must be no higher than one foot above the lowest adjacent grade to the structure. Using human intervention to open a garage door prior to flooding will not satisfy this requirement for automatic openings.

4.46 Storage of Materials and Equipment:

- (a) The storage or processing of materials that are, in time of flooding, flammable, explosive, or potentially injurious to human, animal, or plant life is prohibited.
- (b) Storage of other materials or equipment may be allowed if readily removable from the area within the time available after a flood warning and in accordance with a plan approved by the Governing Body.

4.47 Structural works for flood control that will change the course, current or cross section of protected wetlands or public waters shall be subject to the provisions of Minnesota Statute, Chapter 103G. Community-wide structural works for flood control intended to remove areas from the regulatory flood plain shall not be allowed in the floodway.

4.48 A levee, dike or floodwall constructed in the floodway shall not cause an increase to the 100-year or regional flood and the technical analysis must assume equal conveyance or storage loss on both sides of a stream.

## **SECTION 5.0 FLOOD FRINGE DISTRICT (FF)**

5.1 Permitted Uses: Permitted uses shall be those uses of land or structures listed as permitted uses in the underlying zoning use district(s). If no pre-existing, underlying zoning use districts exist, then any residential or non residential structure or use of a structure or land shall be a permitted use in the Flood Fringe District provided such use does not constitute a public nuisance. All permitted uses shall comply with the standards for Flood Fringe District "Permitted Uses" listed in Section 5.2 and the "Standards for all Flood Fringe Uses" listed in Section 5.5.

### 5.2 Standards for Flood Fringe Permitted Uses:

- 5.21 All structures, including accessory structures, must be elevated on fill so that the lowest floor including basement floor is at or above the regulatory flood protection elevation. The finished fill elevation for structures shall be no lower than one (1) foot below the regulatory flood protection elevation and the fill shall extend at such elevation at least fifteen (15) feet beyond the outside limits of the structure erected thereon.
- 5.22 As an alternative to elevation on fill, accessory structures that constitute a minimal investment and that do not exceed 500 square feet at its largest projection may be internally flood proofed in accordance with Section 4.45 (c).
- 5.23 The cumulative placement of fill where at any one time in excess of one-thousand (1,000) cubic yards of fill is located on the parcel shall be allowable only as a conditional use, unless said fill is specifically intended to elevate a structure in accordance with Section 5.21 of this ordinance.
- 5.24 The storage of any materials or equipment shall be elevated on fill to the regulatory flood protection elevation.
- 5.25 The provisions of Section 5.5 of this Ordinance shall apply.

5.3 Conditional Uses: Any structure that is not elevated on fill or flood proofed in accordance with Section 5.21 - 5.22 and or any use of land that does not comply with the standards in Section 5.23 - 5.24 shall only be allowable as a conditional use. An application for a conditional use shall be subject to the standards and criteria and evaluation procedures specified in Sections 5.4-5.5 and 10.4 of this Ordinance.

### 5.4 Standards for Flood Fringe Conditional Uses:

- 5.41 Alternative elevation methods other than the use of fill may be utilized to elevate a structure's lowest floor above the regulatory flood protection elevation. These alternative methods may include the use of stilts, pilings, parallel walls, etc., or above-grade, enclosed areas such as crawl spaces or tuck under garages. The base or floor of an enclosed area shall be considered above-grade and not a structure's basement or lowest floor if: 1) the enclosed area is above-grade on at least one side of the structure; 2) it is designed to internally flood and is constructed with flood resistant materials; and 3) it is used solely for parking of vehicles, building access or storage. The above-noted alternative elevation methods are subject to the following additional standards:
  - (a) Design and Certification - The structure's design and as-built condition must be certified by a registered professional engineer or architect as being in compliance with the general design

standards of the State Building Code and, specifically, that all electrical, heating, ventilation, plumbing and air conditioning equipment and other service facilities must be at or above the regulatory flood protection elevation or be designed to prevent flood water from entering or accumulating within these components during times of flooding.

- (b) Specific Standards for Above-grade, Enclosed Areas - Above-grade, fully enclosed areas such as crawl spaces or tuck under garages must be designed to internally flood and the design plans must stipulate:
    - (1) A minimum area of openings in the walls where internal flooding is to be used as a flood proofing technique. There shall be a minimum of two openings on at least two sides of the structure and the bottom of all openings shall be no higher than one-foot above grade. The automatic openings shall have a minimum net area of not less than one square inch for every square foot subject to flooding unless a registered professional engineer or architect certifies that a smaller net area would suffice. The automatic openings may be equipped with screens, louvers, valves, or other coverings or devices provided that they permit the automatic entry and exit of flood waters without any form of human intervention; and
    - (2) That the enclosed area will be designed of flood resistant materials in accordance with the FP-3 or FP-4 classifications in the State Building Code and shall be used solely for building access, parking of vehicles or storage.
- 5.42 Basements, as defined by Section 2.812 of this Ordinance, shall be subject to the following:
- (a) Residential basement construction shall not be allowed below the regulatory flood protection elevation.
  - (b) Non-residential basements may be allowed below the regulatory flood protection elevation provided the basement is structurally dry flood proofed in accordance with Section 5.43 of this Ordinance.
- 5.43 All areas of non residential structures including basements to be placed below the regulatory flood protection elevation shall be flood proofed in accordance with the structurally dry flood proofing classifications in the State Building Code. Structurally dry flood proofing must meet the FP-1 or FP-2 flood proofing classification in the State Building Code and this shall require making the structure watertight with the walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effects of buoyancy. Structures flood proofed to the FP-3 or FP-4 classification shall not be permitted.
- 5.44 When at any one time more than 1,000 cubic yards of fill or other similar material is located on a parcel for such activities as on-site storage, landscaping, sand and gravel operations, landfills, roads, dredge spoil disposal or construction of flood control works, an erosion/sedimentation control plan must be submitted unless the community is enforcing a state approved shoreland management ordinance. In the absence of a state approved shoreland ordinance, the plan must clearly specify methods to be used to stabilize the fill on site for a flood event at a minimum of the 100-year or regional flood event. The plan must be prepared and certified by a registered professional engineer or other qualified individual acceptable to the Governing Body. The plan may incorporate alternative procedures for removal of the material from the flood plain if adequate flood warning time exists.
- 5.45 Storage of Materials and Equipment:

- (a) The storage or processing of materials that are, in time of flooding, flammable, explosive, or potentially injurious to human, animal, or plant life is prohibited.
- (b) Storage of other materials or equipment may be allowed if readily removable from the area within the time available after a flood warning and in accordance with a plan approved by the Governing Body.

5.46 The provisions of Section 5.5 of this Ordinance shall also apply.

5.47 Within farmstead ring levee systems, as defined in (c) below, agricultural structures exceeding 500 square feet in size may be constructed with the lowest floor below the regulatory flood protection elevation provided the structure is internally wet floodproofed as outlined in the following floodproofing and administrative provisions:

- (a) For the purposes of this Section, agricultural structures shall be defined as structures related to the growing of crops or raising of livestock. This definition of agricultural structures shall include barns, machine sheds, storage buildings, and garages for the storage of farming machinery and equipment. This definition of agricultural structure does not include a principal or accessory structure to a residential, commercial, or other use not needed for the growing of crops or raising of livestock and shall specifically not include a structure used for human habitation or for parking of non farming related vehicles for the human occupants of structures within the farmstead ring levee system.
- (b) For the purposes of this Section, habitable space (room) is space in a structure used for living, sleeping, eating, or cooking. Bathrooms, toilet compartments, closets, halls, storage rooms, laundry or utility space and similar areas, are not considered habitable space. Further, no space within an agricultural structure constructed in accordance with this Section with a floor below the regulatory flood protection elevation shall be used as habitable space.
- (c) Agricultural structures with the lowest floor below the regulatory flood protection elevation authorized by this Section must be located within the confines of a ring levee system meeting the following criteria:
  - (1) The ring levee system must have been constructed as part of a cost share program of a watershed district established pursuant to Minnesota Statute, Chapter 103D;
  - (2) A registered professional engineer or qualified watershed district staff person must certify that the farmstead ring levee system was constructed in accordance with the design criteria specified by the watershed district as a condition of state/local cost share funding; and
  - (3) The low point of the ring levee system must be at a minimum at least two (2) feet above the flood of record or one (1) foot above the 100-year flood level, whichever is the greater of the two. A registered professional engineer or land surveyor must establish the elevation of the low point of the ring levee system in a datum as specified by the county. A qualified hydrologist, watershed district staff person, or registered professional engineer must establish the 100-year flood elevation and flood of record elevation for the location of the farmstead ring levee system.
- (d) In addition to the permitting and administrative language in this ordinance, the following additional provisions apply to this Section:

- (1) The application materials for the conditional use permit must clearly indicate the floodproofing classification that is being proposed and shall include a set of floodproofing plans and specifications prepared by a registered professional engineer or architect;
  - (2) The conditional use permit issued by the community must specify the floodproofing classification that is being authorized and the regulatory flood protection elevation for the site; and
  - (3) After construction of an agricultural structure authorized by this Section, the applicant shall be required to provide certification by a registered professional engineer or architect that the structure was constructed in accordance with the building/floodproofing specifications authorized by Section 5.47 of this Ordinance. Upon completion, the community must issue a certificate of zoning compliance prior to the use of the structure.
- (e) Structural Design:
- (1) The structure must be designed to the FP-3/FP-4 Floodproofing Classification (W-4 spaces only) found in the 1995 version of the US Army Corps of Engineers' document titled "Flood Proofing Regulations," a copy of which is hereby adopted by reference and declared to be a part of this Ordinance. If there is a conflict of terms found in Flood Proofing Regulations and the definition of terms used in this Ordinance, the latter shall prevail;
  - (2) The design of the structure must include a minimum of two openings in the outside walls of the structure to allow for the equalization of hydrostatic flood forces on all spaces inside the outer walls of the structure. The automatic openings shall be placed on at least two sides of the structure and the bottom of all openings shall be placed no higher than one foot above the lowest adjacent grade of the structure. Opening a garage door during flooding is not considered an automatic opening and shall not meet the requirement for automatic openings. The sizing of the automatic openings shall be in accordance with a design certified by a registered professional engineer or architect. Openings may be equipped with screens, louvers, valves, or other coverings or devices provided that they permit the automatic entry and exit of flood waters. In the design of the openings, the engineer or architect may consult the Federal Emergency Management Agency's publication entitled "Openings in Foundation Walls for Buildings in Special Flood Hazard Areas in accordance with the National Flood Insurance Program," a copy of which is hereby adopted by reference and declared to be a part of this ordinance; and
  - (3) Special care must be taken to make sure that all contents stored in the structure are placed in accordance with Chapter 11 of Flood Proofing Regulations." Specifically, the conditional use issued shall indicate those types of chemicals and similar contents for agricultural uses that are: 1) "extremely hazardous (Class XX)" and require prohibition from the floodplain; and 2) "sufficiently hazardous (Class X) and, if stored in the structure, must be stored above the regulatory flood protection elevation.
- (f) The applicant shall be advised in writing that the internal (wet) floodproofing techniques authorized herein will not be credited for insurance rating purposes by the National Flood Insurance Program. Therefore, the lowest floor for flood insurance rating purposes will be the base or floor level of the internally flooded space. Should flood insurance be purchased, the premiums may be extremely expensive.
- (g) A document must be prepared and recorded that references the property in question such that it would appear in the chain of title and clearly states all of the conditions that have stipulated

in the conditional use permit authorizing construction of a structure with the lowest floor below the regulatory flood protection elevation.

#### 5.5 Standards for All Flood Fringe Uses:

- 5.51 All new principal structures must have vehicular access at or above an elevation not more than two (2) feet below the regulatory flood protection elevation. If a variance to this requirement is granted, the Board of Adjustment must specify limitations on the period of use or occupancy of the structure for times of flooding and only after determining that adequate flood warning time and local flood emergency response procedures exist.
- 5.52 Commercial Uses - accessory land uses, such as yards, railroad tracks, and parking lots may be at elevations lower than the regulatory flood protection elevation. However, a permit for such facilities to be used by the employees or the general public shall not be granted in the absence of a flood warning system that provides adequate time for evacuation if the area would be inundated to a depth and velocity such that when multiplying the depth (in feet) times velocity (in feet per second) the product number exceeds four (4) upon occurrence of the regional flood.
- 5.53 Manufacturing and Industrial Uses - measures shall be taken to minimize interference with normal plant operations especially along streams having protracted flood durations. Certain accessory land uses such as yards and parking lots may be at lower elevations subject to requirements set out in Section 5.52 above. In considering permit applications, due consideration shall be given to needs of an industry whose business requires that it be located in flood plain areas.
- 5.54 Fill shall be properly compacted and the slopes shall be properly protected by the use of riprap, vegetative cover or other acceptable method. The Federal Emergency Management Agency (FEMA) has established criteria for removing the special flood hazard area designation for certain structures properly elevated on fill above the 100-year flood elevation - FEMA's requirements incorporate specific fill compaction and side slope protection standards for multi-structure or multi-lot developments. These standards should be investigated prior to the initiation of site preparation if a change of special flood hazard area designation will be requested.
- 5.55 Flood plain developments shall not adversely affect the hydraulic capacity of the channel and adjoining flood plain of any tributary watercourse or drainage system where a floodway or other encroachment limit has not been specified on the Official Zoning Map.
- 5.56 Standards for recreational vehicles are contained in Section 9.3.
- 5.57 All manufactured homes must be securely anchored to an adequately anchored foundation system that resists flotation, collapse and lateral movement. Methods of anchoring may include, but are not to be limited to, use of over-the-top or frame ties to ground anchors. This requirement is in addition to applicable state or local anchoring requirements for resisting wind forces.

## **SECTION 6.0 GENERAL FLOOD PLAIN DISTRICT**

### 6.1 Permissible Uses:

- 6.11 The uses listed in Section 4.1 of this Ordinance shall be permitted uses.
- 6.12 All other uses shall be subject to the floodway/flood fringe evaluation criteria pursuant to Section 6.2 below. Section 4.0 shall apply if the proposed use is in the Floodway District and Section 5.0 shall apply if the proposed use is in the Flood Fringe District.

6.2 Procedures for Floodway and Flood Fringe Determinations Within the General Flood Plain District.

- 6.21 Upon receipt of an application for a permit or other approval within the General Flood Plain District, the applicant shall be required to furnish such of the following information as is deemed necessary by the Zoning Administrator for the determination of the regulatory flood protection elevation and whether the proposed use is within the Floodway or Flood Fringe District.
- (a) A typical valley cross-section(s) showing the channel of the stream, elevation of land areas adjoining each side of the channel, cross-sectional areas to be occupied by the proposed development, and high water information.
  - (b) Plan (surface view) showing elevations or contours of the ground, pertinent structure, fill, or storage elevations, the size, location, and spatial arrangement of all proposed and existing structures on the site, and the location and elevations of streets.
  - (c) Photographs showing existing land uses, vegetation upstream and downstream, and soil types.
  - (d) Profile showing the slope of the bottom of the channel or flow line of the stream for at least 500 feet in either direction from the proposed development.
- 6.22 The applicant shall be responsible to submit one copy of the above information to a designated engineer or other expert person or agency for technical assistance in determining whether the proposed use is in the Floodway or Flood Fringe District and to determine the regulatory flood protection elevation. Procedures consistent with Minnesota Regulations 1983, Parts 6120.5000 - 6120.6200 and 44 Code of Federal Regulations Part 65 shall be followed in this expert evaluation. The designated engineer or expert is strongly encouraged to discuss the proposed technical evaluation methodology with the respective Department of Natural Resources' Area Hydrologist prior to commencing the analysis. The designated engineer or expert shall:
- (a) Estimate the peak discharge of the regional flood.
  - (b) Calculate the water surface profile of the regional flood based upon a hydraulic analysis of the stream channel and overbank areas.
  - (c) Compute the floodway necessary to convey or store the regional flood without increasing flood stages more than 0.5 foot. A lesser stage increase than .5' shall be required if, as a result of the additional stage increase, increased flood damages would result. An equal degree of encroachment on both sides of the stream within the reach shall be assumed in computing floodway boundaries.
- 6.23 The Zoning Administrator shall present the technical evaluation and findings of the designated engineer or expert to the Governing Body. The Governing Body must formally accept the technical evaluation and the recommended Floodway and/or Flood Fringe District boundary or deny the permit application. The Governing Body, prior to official action, may submit the application and all supporting data and analyses to the Federal Emergency Management Agency, the Department of Natural Resources or the Planning Commission for review and comment. Once the Floodway and Flood Fringe District Boundaries have been determined, the Governing Body shall refer the matter back to the Zoning Administrator who shall process the permit application consistent with the applicable provisions of Section 4.0 and 5.0 of this Ordinance.

## **SECTION 7.0 SUBDIVISIONS<sup>2</sup>**

**<sup>2</sup>Note: This Section is not intended as a substitute for a comprehensive city or county subdivision ordinance. It can, however, be used as an interim control until the comprehensive subdivision ordinance can be amended to include necessary flood plain management provisions.**

7.1 Review Criteria: No land shall be subdivided which is unsuitable for the reason of flooding, inadequate drainage, water supply or sewage treatment facilities. All lots within the flood plain districts shall be able to contain a building site outside of the Floodway District at or above the regulatory flood protection elevation. All subdivisions shall have water and sewage treatment facilities that comply with the provisions of this Ordinance and have road access both to the subdivision and to the individual building sites no lower than two feet below the regulatory flood protection elevation. For all subdivisions in the flood plain, the Floodway and Flood Fringe District boundaries, the regulatory flood protection elevation and the required elevation of all access roads shall be clearly labeled on all required subdivision drawings and platting documents.

7.2 Floodway/Flood Fringe Determinations in the General Flood Plain District: In the General Flood Plain District, applicants shall provide the information required in Section 6.2 of this Ordinance to determine the 100-year flood elevation, the Floodway and Flood Fringe District boundaries and the regulatory flood protection elevation for the subdivision site.

7.3 Removal of Special Flood Hazard Area Designation: The Federal Emergency Management Agency (FEMA) has established criteria for removing the special flood hazard area designation for certain structures properly elevated on fill above the 100-year flood elevation. FEMA's requirements incorporate specific fill compaction and side slope protection standards for multi-structure or multi-lot developments. These standards should be investigated prior to the initiation of site preparation if a change of special flood hazard area designation will be requested.

## **SECTION 8.0 PUBLIC UTILITIES, RAILROADS, ROADS, AND BRIDGES**

8.1 Public Utilities. All public utilities and facilities such as gas, electrical, sewer, and water supply systems to be located in the flood plain shall be flood proofed in accordance with the State Building Code or elevated to above the regulatory flood protection elevation.

8.2 Public Transportation Facilities. Railroad tracks, roads, and bridges to be located within the flood plain shall comply with Sections 4.0 and 5.0 of this Ordinance. Elevation to the regulatory flood protection elevation shall be provided where failure or interruption of these transportation facilities would result in danger to the public health or safety or where such facilities are essential to the orderly functioning of the area. Minor or auxiliary roads or railroads may be constructed at a lower elevation where failure or interruption of transportation services would not endanger the public health or safety.

8.3 On-site Sewage Treatment and Water Supply Systems: Where public utilities are not provided: 1) On-site water supply systems must be designed to minimize or eliminate infiltration of flood waters into the systems; and 2) New or replacement on-site sewage treatment systems must be designed to minimize or eliminate infiltration of flood waters into the systems and discharges from the systems into flood waters and they shall not be subject to impairment or contamination during times of flooding. Any sewage treatment system designed in accordance with the State's current statewide standards for on-site sewage treatment systems shall be determined to be in compliance with this Section.

## **SECTION 9.0 MANUFACTURED HOMES AND MANUFACTURED HOME PARKS AND PLACEMENT OF RECREATIONAL VEHICLES.**

9.1 New manufactured home parks and expansions to existing manufactured home parks shall be subject to the provisions placed on subdivisions by Section 7.0 of this Ordinance.

9.2 The placement of new or replacement manufactured homes in existing manufactured home parks or on individual lots of record that are located in flood plain districts will be treated as a new structure and may be placed only if elevated in compliance with Section 5.0 of this Ordinance. If vehicular road access for pre-existing manufactured home parks is not provided in accordance with Section 5.51, then replacement manufactured homes will not be allowed until the property owner(s) develops a flood warning emergency plan acceptable to the Governing Body.

9.21 All manufactured homes must be securely anchored to an adequately anchored foundation system that resists flotation, collapse and lateral movement. Methods of anchoring may include, but are not to be limited to, use of over-the-top or frame ties to ground anchors. This requirement is in addition to applicable state or local anchoring requirements for resisting wind forces.

9.3 Recreational vehicles that do not meet the exemption criteria specified in Section 9.31 below shall be subject to the provisions of this Ordinance and as specifically spelled out in Sections 9.33-9.34 below.

9.31 Exemption - Recreational vehicles are exempt from the provisions of this Ordinance if they are placed in any of the areas listed in Section 9.32 below and further they meet the following criteria:

- (a) Have current licenses required for highway use.
- (b) Are highway ready meaning on wheels or the internal jacking system, are attached to the site only by quick disconnect type utilities commonly used in campgrounds and recreational vehicle parks and the recreational vehicle has no permanent structural type additions attached to it.
- (c) The recreational vehicle and associated use must be permissible in any pre-existing, underlying zoning use district.

9.32 Areas Exempted For Placement of Recreational Vehicles:

- (a) Individual lots or parcels of record.
- (b) Existing commercial recreational vehicle parks or campgrounds.
- (c) Existing condominium type associations.

9.33 Recreational vehicles exempted in Section 9.31 lose this exemption when development occurs on the parcel exceeding \$1000 dollars for a structural addition to the recreational vehicle or for an accessory structure such as a garage or storage building. The recreational vehicle and all additions and accessory structures will then be treated as a new structure and shall be subject to the elevation/flood proofing requirements and the use of land restrictions specified in Sections 4.0 and 5.0 of this Ordinance. There shall be no development or improvement on the parcel or attachment to the recreational vehicle that hinders the removal of the recreational vehicle to a flood free location should flooding occur.

- 9.34 New commercial recreational vehicle parks or campgrounds and new residential type subdivisions and condominium associations and the expansion of any existing similar use exceeding five (5) units or dwelling sites shall be subject to the following:
- (a) Any new or replacement recreational vehicle will be allowed in the Floodway or Flood Fringe Districts provided said recreational vehicle and its contents are placed on fill above the regulatory flood protection elevation and proper elevated road access to the site exists in accordance with Section 5.51 of this Ordinance. No fill placed in the floodway to meet the requirements of this Section shall increase flood stages of the 100-year or regional flood.
  - (b) All new or replacement recreational vehicles not meeting the criteria of (a) above may, as an alternative, be allowed as a conditional use if in accordance with the following provisions and the provisions of 10.4 of the Ordinance. The applicant must submit an emergency plan for the safe evacuation of all vehicles and people during the 100 year flood. Said plan shall be prepared by a registered engineer or other qualified individual, shall demonstrate that adequate time and personnel exist to carry out the evacuation, and shall demonstrate the provisions of Section 9.31 (a) and (b) of this Ordinance will be met. All attendant sewage and water facilities for new or replacement recreational vehicles must be protected or constructed so as to not be impaired or contaminated during times of flooding in accordance with Section 8.3 of this Ordinance.

## **SECTION 10.0 ADMINISTRATION**

10.1 Zoning Administrator: A Zoning Administrator or other official designated by the Governing Body shall administer and enforce this Ordinance. If the Zoning Administrator finds a violation of the provisions of this Ordinance the Zoning Administrator shall notify the person responsible for such violation in accordance with the procedures stated in Section 12.0 of the Ordinance.

### 10.2 Permit Requirements:

- 10.21 Permit Required. A Permit issued by the Zoning Administrator in conformity with the provisions of this Ordinance shall be secured prior to the erection, addition, or alteration of any building, structure, or portion thereof; prior to the use or change of use of a building, structure, or land; prior to the construction of a dam, or on-site septic system; prior to the change or extension of a nonconforming use; and prior to the placement of fill, excavation of materials, or the storage of materials or equipment within the flood plain.
- 10.22 Application for Permit. Application for a permit shall be made in duplicate to the Zoning Administrator on forms furnished by the Zoning Administrator and shall include the following where applicable: plans in duplicate drawn to scale, showing the nature, location, dimensions, and elevations of the lot; existing or proposed structures, fill, or storage of materials; and the location of the foregoing in relation to the stream channel.
- 10.23 State and Federal Permits. Prior to granting a permit or processing an application for a conditional use permit or variance, the Zoning Administrator shall determine that the applicant has obtained all necessary state and federal permits.
- 10.24 Certificate of Zoning Compliance for a New, Altered, or Nonconforming Use. It shall be unlawful to use, occupy, or permit the use or occupancy of any building or premises or part thereof hereafter created, erected, changed, converted, altered, or enlarged in its use or structure until a

certificate of zoning compliance shall have been issued by the Zoning Administrator stating that the use of the building or land conforms to the requirements of this Ordinance.

- 10.25 Construction and Use to be as Provided on Applications, Plans, Permits, Variances and Certificates of Zoning Compliance. Permits, conditional use permits, or certificates of zoning compliance issued on the basis of approved plans and applications authorize only the use, arrangement, and construction set forth in such approved plans and applications, and no other use, arrangement, or construction. Any use, arrangement, or construction at variance with that authorized shall be deemed a violation of this Ordinance, and punishable as provided by Section 12.0 of this Ordinance.
- 10.26 Certification. The applicant shall be required to submit certification by a registered professional engineer, registered architect, or registered land surveyor that the finished fill and building elevations were accomplished in compliance with the provisions of this Ordinance. Flood proofing measures shall be certified by a registered professional engineer or registered architect.
- 10.27 Record of First Floor Elevation. The Zoning Administrator shall maintain a record of the elevation of the lowest floor (including basement) of all new structures and alterations or additions to existing structures in the flood plain. The Zoning Administrator shall also maintain a record of the elevation to which structures or alterations and additions to structures are flood proofed.
- 10.28 Notifications for Watercourse Alterations. The Zoning Administrator shall notify, in riverine situations, adjacent communities and the Commissioner of the Department of Natural Resources prior to the community authorizing any alteration or relocation of a watercourse. If the applicant has applied for a permit to work in the beds of public waters pursuant to Minnesota Statute, Chapter 103G, this shall suffice as adequate notice to the Commissioner of Natural Resources. A copy of said notification shall also be submitted to the Chicago Regional Office of the Federal Emergency Management Agency (FEMA).
- 10.29 Notification to FEMA When Physical Changes Increase or Decrease the 100-year Flood Elevation. As soon as is practicable, but not later than six (6) months after the date such supporting information becomes available, the Zoning Administrator shall notify the Chicago Regional Office of FEMA of the changes by submitting a copy of said technical or scientific data.

### 10.3 Board of Adjustment:

- 10.31 Rules. The Board of Adjustment shall adopt rules for the conduct of business and may exercise all of the powers conferred on such Boards by State law.
- 10.32 Administrative Review. The Board of Adjustment shall hear and decide appeals where it is alleged there is error in any order, requirement, decision, or determination made by an administrative official in the enforcement or administration of this Ordinance.
- 10.33 Variances. The Board of Adjustment may authorize upon appeal in specific cases such relief or variance from the terms of this Ordinance as will not be contrary to the public interest and only for those circumstances such as hardship, practical difficulties or circumstances unique to the property under consideration, as provided for in the respective enabling legislation for planning and zoning for cities or counties as appropriate. In the granting of such variance, the Board of Adjustment shall clearly identify in writing the specific conditions that existed consistent with the criteria

specified in this Ordinance, any other zoning regulations in the Community, and in the respective enabling legislation that justified the granting of the variance. No variance shall have the effect of allowing in any district uses prohibited in that district, permit a lower degree of flood protection than the regulatory flood protection elevation for the particular area, or permit standards lower than those required by state law. The following additional variance criteria of the Federal Emergency Management Agency must be satisfied:

- (a) Variances shall not be issued by a community within any designated regulatory floodway if any increase in flood levels during the base flood discharge would result.
- (b) Variances shall only be issued by a community upon (i) a showing of good and sufficient cause, (ii) a determination that failure to grant the variance would result in exceptional hardship to the applicant, and (iii) a determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, extraordinary public expense, create nuisances, cause fraud on or victimization of the public, or conflict with existing local laws or ordinances.
- (c) Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief.

10.34 Hearings. Upon filing with the Board of Adjustment of an appeal from a decision of the Zoning Administrator, or an application for a variance, the Board of Adjustment shall fix a reasonable time for a hearing and give due notice to the parties in interest as specified by law. The Board of Adjustment shall submit by mail to the Commissioner of Natural Resources a copy of the application for proposed variances sufficiently in advance so that the Commissioner will receive at least ten days notice of the hearing.

10.35 Decisions. The Board of Adjustment shall arrive at a decision on such appeal or variance within forty-five (45) days. In passing upon an appeal, the Board of Adjustment may, so long as such action is in conformity with the provisions of this Ordinance, reverse or affirm, wholly or in part, or modify the order, requirement, decision or determination of the Zoning Administrator or other public official. It shall make its decision in writing setting forth the findings of fact and the reasons for its decisions. In granting a variance the Board of Adjustment may prescribe appropriate conditions and safeguards such as those specified in Section 10.46, which are in conformity with the purposes of this Ordinance. Violations of such conditions and safeguards, when made a part of the terms under which the variance is granted, shall be deemed a violation of this Ordinance punishable under Section 12.0. A copy of all decisions granting variances shall be forwarded by mail to the Commissioner of Natural Resources within ten (10) days of such action.

10.36 Appeals. Appeals from any decision of the Board of Adjustment may be made, and as specified in this community's official controls and also by Minnesota Statutes.

10.37 Flood Insurance Notice and Record Keeping. The Zoning Administrator shall notify the applicant for a variance that: 1) The issuance of a variance to construct a structure below the base flood level will result in increased premium rates for flood insurance up to amounts as high as \$25 for \$100 of insurance coverage and 2) Such construction below the 100-year or regional flood level increases risks to life and property. Such notification shall be maintained with a record of all variance actions. A community shall maintain a record of all variance actions, including justification for their issuance, and report such variances issued in its annual or biennial report submitted to the Administrator of the National Flood Insurance Program.

10.4 Conditional Uses. The County Board of Commissioners shall hear and decide applications for conditional uses permissible under this Ordinance. Applications shall be submitted to the Zoning Administrator who shall forward the application to the County Board of Commissioners for consideration.

10.41 Hearings. Upon filing with the County Board of Commissioners an application for a conditional use permit, the County Board of Commissioners shall submit by mail to the Commissioner of Natural Resources a copy of the application for proposed conditional use sufficiently in advance so that the Commissioner will receive at least ten days notice of the hearing.

10.42 Decisions. The County Board of Commissioners shall arrive at a decision on a conditional use within forty-five (45) days. In granting a conditional use permit the County Board of Commissioners shall prescribe appropriate conditions and safeguards, in addition to those specified in Section 10.46, which are in conformity with the purposes of this Ordinance. Violations of such conditions and safeguards, when made a part of the terms under which the conditional use permit is granted, shall be deemed a violation of this Ordinance punishable under Section 12.0. A copy of all decisions granting conditional use permits shall be forwarded by mail to the Commissioner of Natural Resources within ten (10) days of such action.

10.43 Procedures to be followed by the County Board of Commissioners in Passing on Conditional Use Permit Applications Within all Flood Plain Districts.

- (a) Require the applicant to furnish such of the following information and additional information as deemed necessary by the County Board of Commissioners for determining the suitability of the particular site for the proposed use:
  - (1) Plans in triplicate drawn to scale showing the nature, location, dimensions, and elevation of the lot, existing or proposed structures, fill, storage of materials, flood proofing measures, and the relationship of the above to the location of the stream channel; and
  - (2) Specifications for building construction and materials, flood proofing, filling, dredging, grading, channel improvement, storage of materials, water supply and sanitary facilities.
- (b) Transmit one copy of the information described in subsection (a) to a designated engineer or other expert person or agency for technical assistance, where necessary, in evaluating the proposed project in relation to flood heights and velocities, the seriousness of flood damage to the use, the adequacy of the plans for protection, and other technical matters.
- (c) Based upon the technical evaluation of the designated engineer or expert, the County Board of Commissioners shall determine the specific flood hazard at the site and evaluate the suitability of the proposed use in relation to the flood hazard.

10.44 Factors Upon Which the Decision of the County Board of Commissioners Shall Be Based. In passing upon conditional use applications, the County Board of Commissioners shall consider all relevant factors specified in other sections of this Ordinance, and:

- (a) The danger to life and property due to increased flood heights or velocities caused by encroachments.
- (b) The danger that materials may be swept onto other lands or downstream to the injury of others or they may block bridges, culverts or other hydraulic structures.
- (c) The proposed water supply and sanitation systems and the ability of these systems to prevent disease, contamination, and unsanitary conditions.
- (d) The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owner.
- (e) The importance of the services provided by the proposed facility to the community.
- (f) The requirements of the facility for a waterfront location.

- (g) The availability of alternative locations not subject to flooding for the proposed use.
- (h) The compatibility of the proposed use with existing development and development anticipated in the foreseeable future.
- (i) The relationship of the proposed use to the comprehensive plan and flood plain management program for the area.
- (j) The safety of access to the property in times of flood for ordinary and emergency vehicles.
- (k) The expected heights, velocity, duration, rate of rise, and sediment transport of the flood waters expected at the site.
- (l) Such other factors which are relevant to the purposes of this Ordinance.

10.45 Time for Acting on Application. The County Board of Commissioners shall act on an application in the manner described above within forty-five (45) days from receiving the application, except that where additional information is required pursuant to 10.43 of this Ordinance. The County Board of Commissioners shall render a written decision within thirty (30) days from the receipt of such additional information.

10.46 Conditions Attached to Conditional Use Permits. Upon consideration of the factors listed above and the purpose of this Ordinance, the County Board of Commissioners shall attach such conditions to the granting of conditional use permits as it deems necessary to fulfill the purposes of this Ordinance. Such conditions may include, but are not limited to, the following:

- (a) Modification of waste treatment and water supply facilities.
- (b) Limitations on period of use, occupancy, and operation.
- (c) Imposition of operational controls, sureties, and deed restrictions.
- (d) Requirements for construction of channel modifications, compensatory storage, dikes, levees, and other protective measures.
- (e) Flood proofing measures, in accordance with the State Building Code and this Ordinance. The applicant shall submit a plan or document certified by a registered professional engineer or architect that the flood proofing measures are consistent with the regulatory flood protection elevation and associated flood factors for the particular area.

## **SECTION 11.0 NONCONFORMING USES**

11.1 A structure or the use of a structure or premises which was lawful before the passage or amendment of this Ordinance but which is not in conformity with the provisions of this Ordinance may be continued subject to the following conditions.

11.11 No such use shall be expanded, changed, enlarged, or altered in a way that increases its nonconformity.

11.12 Any structural alteration or addition to a nonconforming structure or nonconforming use which would result in increasing the flood damage potential of that structure or use shall be protected to the Regulatory Flood Protection Elevation in accordance with any of the elevation on fill or flood proofing techniques (i.e., FP-1 thru FP-4 floodproofing classifications) allowable in the State Building Code, except as further restricted in 11.13 below.

11.13 The cost of any structural alterations or additions to any nonconforming structure over the life of the structure shall not exceed 50 percent of the market value of the structure unless the conditions of this Section are satisfied. The cost of all structural alterations and additions constructed since

the adoption of the Community's initial flood plain controls must be calculated into today's current cost which will include all costs such as construction materials and a reasonable cost placed on all manpower or labor. If the current cost of all previous and proposed alterations and additions exceeds 50 percent of the current market value of the structure, then the structure must meet the standards of Section 4.0 or 5.0 of this Ordinance for new structures depending upon whether the structure is in the Floodway or Flood Fringe District, respectively.

11.14 If any nonconforming use is discontinued for 12 consecutive months, any future use of the building premises shall conform to this Ordinance. The Assessor shall notify the Zoning Administrator in writing of instances of nonconforming uses that have been discontinued for a period of 12 months.

11.15 If any nonconforming use or structure is destroyed by any means, including floods, to an extent of 50 percent or more of its market value at the time of destruction, it shall not be reconstructed except in conformity with the provisions of this Ordinance. The applicable provisions for establishing new uses or new structures in Sections 4.0, 5.0 or 6.0 will apply depending upon whether the use or structure is in the Floodway, Flood Fringe or General Flood Plain District, respectively.

## **SECTION 12.0 PENALTIES FOR VIOLATION**

12.1 Violation of the provisions of this Ordinance or failure to comply with any of its requirements (including violations of conditions and safeguards established in connection with grants of variances or conditional uses) shall constitute a misdemeanor and shall be punishable as defined by law.

12.2 Nothing herein contained shall prevent the County of Marshall from taking such other lawful action as is necessary to prevent or remedy any violation. Such actions may include but are not limited to:

12.21 In responding to a suspected Ordinance violation, the Zoning Administrator and Local Government may utilize the full array of enforcement actions available to it including but not limited to prosecution and fines, injunctions, after-the-fact permits, orders for corrective measures or a request to the National Flood Insurance Program for denial of flood insurance availability to the guilty party. The Community must act in good faith to enforce these official controls and to correct Ordinance violations to the extent possible so as not to jeopardize its eligibility in the National Flood Insurance Program.

12.22 When an Ordinance violation is either discovered by or brought to the attention of the Zoning Administrator, the Zoning Administrator shall immediately investigate the situation and document the nature and extent of the violation of the official control. As soon as is reasonably possible, this information will be submitted to the appropriate Department of Natural Resources' and Federal Emergency Management Agency Regional Office along with the Community's plan of action to correct the violation to the degree possible.

12.23 The Zoning Administrator shall notify the suspected party of the requirements of this Ordinance and all other official controls and the nature and extent of the suspected violation of these controls. If the structure and/or use is under construction or development, the Zoning Administrator may order the construction or development immediately halted until a proper permit or approval is granted by the Community. If the construction or development is already completed, then the Zoning Administrator may either: (1) issue an order identifying the corrective actions that must be

made within a specified time period to bring the use or structure into compliance with the official controls; or (2) notify the responsible party to apply for an after-the-fact permit/development approval within a specified period of time not to exceed 30-days.

12.24 If the responsible party does not appropriately respond to the Zoning Administrator within the specified period of time, each additional day that lapses shall constitute an additional violation of this Ordinance and shall be prosecuted accordingly. The Zoning Administrator shall also upon the lapse of the specified response period notify the landowner to restore the land to the condition which existed prior to the violation of this Ordinance.

### **SECTION 13.0 AMENDMENTS**

The flood plain designation on the Official Zoning Map shall not be removed from flood plain areas unless it can be shown that the designation is in error or that the area has been filled to or above the elevation of the regulatory flood protection elevation and is contiguous to lands outside the flood plain. Special exceptions to this rule may be permitted by the Commissioner of Natural Resources if he determines that, through other measures, lands are adequately protected for the intended use.

All amendments to this Ordinance, including amendments to the Official Zoning Map, must be submitted to and approved by the Commissioner of Natural Resources prior to adoption. Changes in the Official Zoning Map must meet the Federal Emergency Management Agency's (FEMA) Technical Conditions and Criteria and must receive prior FEMA approval before adoption. The Commissioner of Natural Resources must be given 10-days written notice of all hearings to consider an amendment to this Ordinance and said notice shall include a draft of the Ordinance amendment or technical study under consideration.

### **SECTION 14.0 FORCE AND EFFECT**

The Flood Plain Ordinance shall be in full force and effect immediately upon adoption by the Marshall County Board of Commissioners and shall continue to be in full force and effect until amended or discontinued.

Amended ordinance adopted by the Marshall County Board of Commissioners

This \_\_\_\_\_ of \_\_\_\_\_, \_\_\_\_\_  
(Day) (Month) (Year)

Attest: \_\_\_\_\_, Marshall County Board Chairperson

Attest: \_\_\_\_\_,  
Scott Peters  
Marshall County Auditor &  
Executive Secretary to the County Board

Stamp With Community Seal